

1000VA Solar Inverter



Product Specifications

Parameters	1000VA (Output Power – 800 W @ UPF)	
	Narrow voltage	Wide voltage
1. Voltage:		
- Mains AC lower voltage cut / Recovery	180 ± 5 V / 190 ± 5 V	100 ± 5 V / 110 ± 5 V
- Mains AC Higher voltage cut / Recovery	265 ± 5 V / 255 ± 5 V	285 ± 5 V / 275 ± 5 V
2. Battery charging voltage range (AC Mains)	180 V AC to 265 V AC	100 V AC to 285 V AC
3. Output voltage (Inverter mode)without load	230 ± 3 V	230 ± 3 V
4. Change over time (AC Mains to Inverter)	< 10 milli-sec	< 30 milli-sec
5. Battery Charging (AC Mains):		
No. of Batteries	Double(2x12V –Connected in Series)	
Charging Current	12 ± 1 amps	
‘Boost Charging’ voltage	28.8 ± 0.2 V	
‘Float Charging’ voltage	27.6 ± 0.2 V	
Charging methodology (AC Mains)	Constant current followed by constant voltage	
Battery lower voltage cut-off	21.6 ± 0.2 V	
6. SPV Charging (PWM Charge Controller):		
Nominal SPV input voltage	24V DC	
Max. SPV input voltage	50V DC	

1000VA Solar Inverter



Float Charge	27.4V DC (25 deg. C
Main Charge	28.8V DC (25 deg. C), 30 min. (daily)
Boost charge	28.8V DC (25 deg. C), 2 h
Equalisation	29.6V DC (25 deg. C), 2 h
Max. charge current	40.0 A
Recommended Battery Capacity	80 AH to 180AH (Flat Paste Flooded or Tubular)
7. Output Wave form	Pure Sine Wave
8. Output frequency	Same as input when AC mains available & 50.0 ± 0.5 Hz on UPS
9. Efficiency	AC to DC : ≥ 75% DC to AC : ≥75%
10. Operating Environment	0 deg. C to 50 deg. C
11. LED indications	SPV ON, Mains, Charging, UPS ON, Low battery & Over load
12. Audible Alarm	Low battery, Over load & Short circuit
13. Protections:	
Over load	100 + 5% load on UPS (auto reset if reduce the load within 3 re-try)
Over charge	Protects the battery from overcharging by controlling the charging current & voltage
Short circuit	Shutdown when AC mains is not there and AC fuse / MCB trips when AC mains is available
Thermal shutdown	Above 93 deg. C inside the unit
Battery reverse polarity	Protects the UPS and DC fuses blown on PMB
Battery deep discharge	Protects the battery from deep discharge having cut-off at 10.8 ± 0.2 V per battery
14. Mechanical Details:	
Cabinet	Metal front facia with metal cabinet (Sticker design as per the

1000VA Solar Inverter



	approved sample shared by Mktg)
Cabinet Colour	White
Dimensions (All dimensions in mm)	Without Carton Box: 1000VA (800W) : 290 (L) X 327 (W) X 150 (H)
Carton Box	Plain white
15. Recommended Loads	Light, Fan & Television